



BEARING BOWER CORP.

4.331 Inch | 110.007 Millimeter x 2.1250 in x 16.5 in TIMKEN SDAF 22222 Pillow Block Bearings



Bearing No. SDAF 22222

SDAF 22222 Bearing 2D drawings and 3D CAD models

Category	Pillow Block Bearings
Inventory	0.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	49.49
EAN	0087796307995
Product Group	M06288
Number of Mounting Holes	4
Mounting Method	Shaft Mount
Housing Style	4 Bolt Pillow Block
Rolling Element	Spherical Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	7/8 Inch
Relubricatable	Yes
Insert Part Number	22222
Seals	Triple Ring Labyrinth
Housing Configuration	2 Piece Split
Inch - Metric	Inch
Other Features	Double Row Heavy Duty Straight Bore
Long Description	4 Bolt Pillow Block; 4.331" Bore; 4-15/16" Base to Center Height; Shaft Mount Mount; Spherical Roller Bearing; 12-5/8" Minimum



BEARING BOWER CORP.

	Bolt Spacing; 14-1/2" Bolt Spacing Maximum; Relubrica
Category	Pillow Block
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Pillow Block
Manufacturer URL	http://www.timken.com
Manufacturer Item Number	SDAF 22222
Weight / LBS	109
B	4.938 Inch 125.425 Millimeter
Actual Bolt Center to Center	0 Inch 0Millimeter
D	7.25 Inch 184.15 Millimeter
Nominal Bolt Center to Center	13.6 Inch 344.5 Millimeter
Bolt Spacing Minimum	12.625 Inch 320.675Millimeter
Bolt Spacing Maximum	14.5 Inch 368.3Millimeter
d	4.331 Inch 110.007 Millimeter
Diameter S-2	4 7/8 in
Diameter S-3	4 3/16 in
A	4.9375 in
B	16.5 in
C	6.750 in
D	2.1250 in
E Max.	14.5000 in
E Min.	12.6250 in
F	4.00 in
H ¹	9.8750 in
Oil Level K	1.8750 in



BEARING BOWER CORP.

L ²	7.250 in
Y	1.9531 in
No. of Base Bolts Required	4
Bolt Hole Length	1.8125 in
Bolt Hole Width	0.875 in
Size of Base Bolts Required	0.875 in
Locknut	AN22
Lockwasher	W22
Housing Only ³	SDAF222
Stabilizing Ring 1 Req ' d ⁴	SR-22-19
Triple Seal 2 Req ' d at S-2	LOR121
Triple Seal 2 Req ' d at S-3	LOR113
Assembly Weight	109.0 lb
Full Timken Part Number	SDAF22222